

SCM Series Electro Metabo Type Pipe Cutting and Beveling Machine 25-1430mm



Model: SCM89-SCM1430
230V-50/60Hz 2400W 11A
N 6600/Min(RPM)
Working Range: 25-1430mm
Rotation Speed: 8-50r/min
Working Range: 3/4"-3"-48"-56"
Wall Thickness: ≤35
Motor: Electric Motor
Body: Steel/Aluminum
Cutting Mode: Cold Cut/Wire Cutting
Brand: SAIVS
Country of Origin: China

| Model | Working Range(mm) | Working Range(inch) | Wall Thickness | Rotation Speed |
|----------|-------------------|---------------------|----------------|----------------|
| SCM-89 | 25-89 | 3/4"-3" | ≤35mm | 50r/min |
| SCM-159 | 50-159 | 2"-5" | ≤35mm | 21r/min |
| SCM-168 | 50-168 | 2"-6" | ≤35mm | 21r/min |
| SCM-230 | 80-230 | 3"-8" | ≤35mm | 20r/min |
| SCM-275 | 125-275 | 5"-10" | ≤35mm | 20r/min |
| SCM-305 | 150-305 | 6"-10" | ≤35mm | 18r/min |
| SCM-325 | 168-325 | 6"-12" | ≤35mm | 16r/min |
| SCM-377 | 219-377 | 8"-14" | ≤35mm | 13r/min |
| SCM-426 | 273-426 | 10"-16" | ≤35mm | 12r/min |
| SCM-457 | 300-457 | 12"-18" | ≤35mm | 12r/min |
| SCM-508 | 355-508 | 14"-20" | ≤35mm | 12r/min |
| SCM-560 | 400-560 | 16"-22" | ≤35mm | 12r/min |
| SCM-610 | 457-610 | 18"-24" | ≤35mm | 11r/min |
| SCM-630 | 480-630 | 20"-24" | ≤35mm | 11r/min |
| SCM-660 | 508-660 | 20"-26" | ≤35mm | 11r/min |
| SCM-715 | 560-715 | 22"-28" | ≤35mm | 10r/min |
| SCM-762 | 600-762 | 24"-30" | ≤35mm | 10r/min |
| SCM-830 | 680-830 | 26"-32" | ≤35mm | 10r/min |
| SCM-914 | 762-914 | 30"-36" | ≤35mm | 10r/min |
| SCM-1066 | 914-1066 | 36"-42" | ≤35mm | 9r/min |
| SCM-1230 | 1066-1230 | 42"-48" | ≤35mm | 9r/min |
| SCM-1430 | 1230-1430 | 48"-56" | ≤35mm | 8r/min |

SCH Series 25-1630mm Hydraulic Pipe Cutting and Beveling Machine



Model: SCH89-SCH1630
Processing Range: 25-1630mm
Rotation Speed: 7-42r/min
Power Supply: 380-440V 3PH 50/60Hz 5-30L/min @ 10Mpa
Working Range: 3/4"-3"-56"-64" inches
Wall Thickness: ≤35/40
Power Source: Hydraulic
Automatic Grade: Automatic
Bevel Type: V, U, J Compound bevel, Counter boring
FUNCTIONS: Pipe cold cutting, bevelling, facing
Body: Steel/Aluminum
Country of Origin: China



| Ordinary Type Hydraulic Station | |
|---------------------------------|-------------------------|
| Power Supply | 5.5KW |
| Working Voltage | 380V, 3PH, 5 Lines |
| Working Frequency | 50HZ |
| Rated Working Pressure | 10Mpa |
| Rated Flowing | 25L/min |
| Open Way | Manual / Remote Control |
| Oil Line Length | 6m (Standard) |
| Net Weight (KG) | 220KGS |



| PLC Type Hydraulic Station | |
|----------------------------|-------------------------|
| Power Supply | 5.5KW |
| Working Voltage | 380V, 3PH, 5 Lines |
| Working Frequency | 50HZ |
| Rated Working Pressure | 10Mpa |
| Rated Flowing | 5-30L/min |
| Control System | PLC Control |
| Working Speed | Remote Control |
| Control Panel | Electronic Display |
| Open Way | Manual / Remote Control |
| Oil Line Length | 6m (Standard) |
| Net Weight (KG) | 239KGS |

SCP Series 25-1230mm Pneumatic Pipe Cutting and Beveling Machine



Model: SCP89-SCP1230
Processing Range: 25-1230mm
Rotation Speed: 220r/min
Torque: 115NM
Power: 3.5HP
Air Pressure: 0.8-1.0Mpa
Air Consumption: 1000-2000L/min
Working Range: 3/4"-3"-42"-48"
Wall Thickness: ≤35
Power Source: Pneumatic
Control: Automatic
Body: Steel/Aluminum
Country of Origin: China

| Model | Working Range(mm) | Working Range(inch) | Wall Thickness | Rotation Speed | Air Working Pressure | Air Consumption |
|----------|-------------------|---------------------|----------------|----------------|----------------------|-----------------|
| SCP-89 | 25-89 | 3/4"-3" | ≤35 | 50r/min | 0.6Mpa | 1500L/min |
| SCP-168 | 50-168 | 2"-6" | ≤35 | 21r/min | 0.6Mpa | 1500L/min |
| SCP-230 | 80-230 | 3"-8" | ≤35 | 20r/min | 0.6Mpa | 1500L/min |
| SCP-275 | 125-275 | 5"-10" | ≤35 | 20r/min | 0.6Mpa | 1500L/min |
| SCP-305 | 150-305 | 6"-10" | ≤35 | 18r/min | 0.6Mpa | 1500L/min |
| SCP-325 | 168-325 | 6"-12" | ≤35 | 16r/min | 0.6Mpa | 1500L/min |
| SCP-377 | 219-377 | 8"-14" | ≤35 | 13r/min | 0.6Mpa | 1500L/min |
| SCP-426 | 273-426 | 10"-16" | ≤35 | 12r/min | 0.7Mpa | 1800L/min |
| SCP-457 | 300-457 | 12"-18" | ≤35 | 12r/min | 0.7Mpa | 1800L/min |
| SCP-508 | 355-508 | 14"-20" | ≤35 | 12r/min | 0.7Mpa | 1800L/min |
| SCP-560 | 400-560 | 16"-22" | ≤35 | 12r/min | 0.7Mpa | 1800L/min |
| SCP-610 | 457-610 | 18"-24" | ≤35 | 11r/min | 0.7Mpa | 1800L/min |
| SCP-630 | 480-630 | 20"-24" | ≤35 | 11r/min | 0.7Mpa | 1800L/min |
| SCP-660 | 508-660 | 20"-26" | ≤35 | 11r/min | 0.7Mpa | 1800L/min |
| SCP-715 | 560-715 | 22"-28" | ≤35 | 11r/min | 0.7Mpa | 2000L/min |
| SCP-762 | 600-762 | 24"-30" | ≤35 | 11r/min | 0.8Mpa | 2000L/min |
| SCP-830 | 660-813 | 26"-32" | ≤35 | 10r/min | 0.8Mpa | 2000L/min |
| SCP-914 | 762-914 | 30"-36" | ≤35 | 10r/min | 0.8Mpa | 2000L/min |
| SCP-1066 | 914-1066 | 36"-42" | ≤35 | 9r/min | 0.8Mpa | 2000L/min |
| SCP-1230 | 1066-1230 | 42"-48" | ≤35 | 8r/min | 0.8Mpa | 2000L/min |

SCE Series 25-1230mm Electric Pipe Cutting and Beveling Machine



Model: SCE89-SCE1230
Processing Range: 25-1230mm
Voltage: 220~240V
Working Range: 3/4"-3"-42"-48"
Wall Thickness: ≤35
Rotation Speed: 10-42 r/min
Power Source: Electric 1800/2000W
Power Factor: >0.9
Body: Steel/Aluminum
Control: Semi-automatic
Operation Mode: Electric/Pneumatic/Hydraulic Driven
Condition: New
Country of Origin: China

| Model | Processing Range (ID-OD) | Working Range (ID-OD) | Cutting Groove Wall Thickness | The Knife Dish Speed (Rotation Speed) |
|----------|--------------------------|-----------------------|-------------------------------|---------------------------------------|
| SCE-89 | 25-89 | 3/4"-3" | ≤35 | 42r/min |
| SCE-159 | 50-159 | 2"-5" | ≤35 | 20r/min |
| SCE-168 | 50-168 | 2"-6" | ≤35 | 18r/min |
| SCE-230 | 80-230 | 3"-8" | ≤35 | 15r/min |
| SCE-275 | 125-275 | 5"-10" | ≤35 | 14r/min |
| SCE-305 | 150-305 | 6"-10" | ≤35 | 13r/min |
| SCE-325 | 168-325 | 6"-12" | ≤35 | 13r/min |
| SCE-377 | 219-377 | 8"-14" | ≤35 | 12r/min |
| SCE-426 | 273-426 | 10"-16" | ≤35 | 12r/min |
| SCE-457 | 300-457 | 12"-18" | ≤35 | 12r/min |
| SCE-508 | 355-508 | 14"-20" | ≤35 | 12r/min |
| SCE-560 | 400-560 | 16"-22" | ≤35 | 12r/min |
| SCE-610 | 457-610 | 18"-24" | ≤35 | 11r/min |
| SCE-630 | 480-630 | 20"-24" | ≤35 | 11r/min |
| SCE-660 | 508-660 | 20"-26" | ≤35 | 11r/min |
| SCE-715 | 560-715 | 22"-28" | ≤35 | 10r/min |
| SCE-762 | 600-762 | 24"-30" | ≤35 | 10r/min |
| SCE-830 | 660-813 | 26"-32" | ≤35 | 10r/min |
| SCE-914 | 762-914 | 30"-36" | ≤35 | 10r/min |
| SCE-1066 | 914-1066 | 36"-42" | ≤35 | 10r/min |
| SCE-1230 | 1066-1230 | 42"-48" | ≤35 | 10r/min |